



FHI 4000 PROP

PLURAL COMPONENT- HYDRAULIC- HIGH PRESSURE-VARIABLE RATIO METERING UNIT

TECHNICAL DATA

MAXIMUM OUTPUT	:18 l/min.
MINIMUM OUTPUT	: 1 l/min.
MAX HYDRAULIC PRESSURE	: 400 bar
MAX PRESSURE RATING	: 300 bar
ELECTRICAL POWER REQ.	: 14 Kw – 380V. 3 phases + NEUTRAL
TRANSFORMER	: 5000 W.
MAX HOSES LENGTH	: 100 m.

STANDARD EQUIPMENT:

- 82' – 25 meters HEATED HOSES 3/8"
- N° 2 Air driven transfer pumps 3:1
- Recycling valves and tubes.

STANDARD FEATURES

- PARALLEL PUMPS WITH ADJUSTABLE RATIO 100:100 TO 100:30 IN BOTH SIDES
- AUTOMATIC WASHING SYSTEM IN THE ISO SIDE.
- SEPARATE PREHEATERS FOR MAXIMUM EFFICIENCY.
- MATERIAL SUPPLY FILTERS TO AVOID FEELURE IN BALL VALVES
- MAX PRESSURE CUT-OFF VALVES IN BOTH SIDES FOR SAFETY.
- MANUAL VALVES FOR FAST RECYCLING.
- ELECTRONIC CONTROL FOR ISO AND POLY PRE-HEATERS.
- SEPARATE ELECTRONIC CONTROL FOR ISO AND POLY ON HEATED HOSES
- EASY REPLACEMENT OF METERING PUMPS FOR EASY MAINTENANCE.
- N° 4 WHEELS FOR EASY MOVING.
- SUPPORTS FOR TRANSFER PUMPS.

