

### ADVANCED FOAM AND COATING TECHNOLOGY

The industry leader in polyurea hybrid roofing elastomers now brings you an economical and versatile solution for repairing and modifying foam roofs and other applications.

Utilized with our Qwik Spray System, our VFI-711 and VFI-540 Aluminum products will allow you to repair defects and re-foam new penetrations in existing foam roofs without using large cumbersome equipment.

The Qwik Spray System is easier to operate than any other spray system you are currently using for repairs or quick projects. Since these products are filled in 1500 ml cartridges there is no pre-mixing, no mess, and no wasted material. This system provides excellent speed of application, control of your coating thickness and will fill and seal in any repair situation your existing equipment can and more.



#### Product Description:

VFI-711 is two-component spray applied nominal 4-pound rigid polyurethane foam insulation. This foam system has the benefit of precise ratio and fine spray pattern control over froth systems. The primary use, in conjunction with VFI-540 Aluminum, is the portable repair of spray foam roof blisters, delaminating of foam roofs, cracks, test cut areas and repairing modifications to existing foam roofs.

VFI-711 can also be utilized as a stand-alone product as a concrete block cavity fill and structural fill for thermoplastic parts. It can also be used for sealing and insulating of house sills, walls and around windows and doors.


VFI-540 Aluminum is a two-component spray applied polyurea hybrid elastomer, which has protected over 30 million square feet of roofs. VFI-540 Aluminum can be utilized with the Qwik Spray System or applied by heated, plural component spray equipment. VFI-540 Aluminum is designed to be used as a spray applied protective roof coating for use over concrete, metal, polyurethane foam and smooth built-up roofs.



**VOLATILEFREE**INC

THIS INFORMATION AND TECHNICAL ADVICE PROVIDED HEREIN ARE BELIEVED TO BE RELIABLE AND ACCURATE TO THE BEST KNOWLEDGE OF VOLATILE FREE, INC., AS BASED ON TESTS AND SHOULD SERVE ONLY AS A RECOMMENDATION. AS THE MANUFACTURER, VOLATILE FREE, INC. MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESSED, IMPLIED OR STATUTORY, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR USE OR A PARTICULAR PURPOSE FOR THE PRODUCT. VOLATILE FREE, INC. MAKES NO

VFI-540 Aluminum is sold in cases of 6 kits. Each kit contains 1500 ml of material. A case will cover 100 square feet with 38 mls of coating. Included with each kit is a static mixer with an air atomizing tip.



VFI-711 spray foam is sold in cases of 6 kits. A case of VFI-711 will yield 72 board feet. Included with each kit is a static mixer with an air atomizing tip.

#### Additional Applications:

**VFI-Qwik Spray System is the most economical method to repair roofs and other applications.**

#### VFI-711

- Leveling of ponding areas, around penetrations and difficult to reach areas.
- Repair of freezers, hot tubs, HVAC and piping insulation.
- Insulating new, or making repairs to previously insulated trailers.
- Infiltration and radon gas control.
- Installation for mobile home roofs and sub-floors.

#### VFI-540 Aluminum

- Applied over various single-ply membranes.

Call VFI at (800) 307-9218